Subject Index for
Electronics and Communications in Japan, Part 2, Volume 76, 1993

2-Gb/in^2 recording technology: **3**, 94-104

a-Si: **12**, 11-19
a-Si:H film: **7**, 92-94
a-Si:H/a-SiO:H interface: **7**, 92-94
Absolute pressure sensor: **1**, 93-106
Absorption spectrum change: **12**, 110-115
AC-DC converter: **11**, 94-105
Accelerometer: **4**, 73-83
Acicular particles: **2**, 108-113
Active filter: **2**, 83-92
Active matrix: **12**, 20-30
Adhesion: **6**, 59-68
Ag-Pd alloy: **3**, 63-73
Al "direct shunt": **6**, 78-87
Al alloy: **6**, 59-68
Algebraic filtering operations: **12**, 1-10
Amorphous current transformer: **7**, 68-76
Amorphous silica: **10**, 66-73
Amorphous silicon: **11**, 68-77
Amplified spontaneous emission (ASE): **11**, 1-13
Analog image recording: **5**, 73-82
Anodic oxidation: **6**, 99-106
Antenna duplexer: **8**, 48-60
Asymmetric coplanar stripline (ACPS): **1**, 25-34
Asymmetry: **8**, 40-47
ATC: **8**, 40-47
Atomic force microscope (AFM): **12**, 99-110
Atomic-level epitaxy: **2**, 14-22
Attenuation characteristic: **5**, 27-34
Attenuation poles: **8**, 48-60
Autostereoscopic 3D display: **7**, 77-84
Autostereoscopic 3D television display: **8**, 89-98

Bandpass: **7**, 22-30
Barium ferrite: **2**, 108-113
Batch-process packaging: **1**, 93-106
$Ba_{1-x}K_xBiO_3$: **12**, 73-81
Beryllium doping: **6**, 34-41
Bi-CMOS: **3**, 105-113
BiPbSrCaCuO (BPSCCO) superconductor: **8**, 99-109
Biquad filter: **2**, 83-92
Body-effect compensation: **12**, 82-89
Boundary element method: **2**, 43-49
Breakdown voltage: **6**, 99-106
Buffer layer: **1**, 25-34

CAD: **7**, 1-11
Cadmium arachidate: **12**, 99-110
Calorimetry: **11**, 25-33
Capacitive pressure sensor: **1**, 93-106
Capacitive sensor: **4**, 73-83; **7**, 85-91
CCD: **3**, 43-51
Čerenkov instability: **1**, 42-50
Characteristic variation: **3**, 85-93
Chemical beam epitaxy: **6**, 34-41
Chemical oxidative polymerization: **6**, 88-99
Chiral nematic liquid crystal: **12**, 90-98
Cholesteric-nematic phase transition: **12**, 90-98
Circuit theory: **7**, 102-109
Co-Cr medium: **5**, 94-104
Coated magnetic film: **2**, 108-113
Collapse: **7**, 39-46
Colloid-SEM method: **10**, 58-65
Common memory: **2**, 1-13
Complex eigenstate: **3**, 28-35
Complex frequency variable: **7**, 102-109
Complex refractive index: **4**, 51-59
Complex-valued equivalent circuit: **7**, 102-109
Composite magnetic head: **3**, 94-104
Composite material device: **1**, 68-79
III-V Compound semiconductor: **2**, 14-22
Computer algebra: **1**, 1-12, 13-24
Computer simulation: **6**, 107-112
Conductor edges: **10**, 30-38
Conductor thickness: **9**, 1-10
Constant voltage step: **8**, 110-117
Contact material: **3**, 63-73
Cooling efficiency: **1**, 68-79
Coplanar stripline (CPS): **1**, 25-34
Coplanar waveguide (CPW): **1**, 25-34
Cost-performance analysis: **8**, 72-82
CO_2 laser corona preionization: **1**, 35-41
Crystal oscillator: **9**, 61-69
Crystal resonator: **9**, 61-69
Crystallinity: **7**, 95-101
Crystallization: **7**, 39-46
Crystallization phenomena: **10**, 108-116
Cu metallization technology: **2**, 93-100
Current conveyor: **2**, 83-92
Current density: **3**, 20-27
Current mirror: **3**, 105-113
Current sensor: **9**, 80-90
$CuTi_2$ intermetallic compound film: **2**, 93-100
CVD: **12**, 11-19

Damage: **6**, 69-77
Decision feedback: **4**, 84-95
Deep-level trap: **6**, 69-77
Demultiplexing: **7**, 22-30

Subject Index for
Electronics and Communications in Japan, Part 2, Volume 76, 1993

2-Gb/in^2 recording technology: **3**, 94-104

a-Si: **12**, 11-19
a-Si:H film: **7**, 92-94
a-Si:H/a-SiO:H interface: **7**, 92-94
Absolute pressure sensor: **1**, 93-106
Absorption spectrum change: **12**, 110-115
AC-DC converter: **11**, 94-105
Accelerometer: **4**, 73-83
Acicular particles: **2**, 108-113
Active filter: **2**, 83-92
Active matrix: **12**, 20-30
Adhesion: **6**, 59-68
Ag-Pd alloy: **3**, 63-73
Al "direct shunt": **6**, 78-87
Al alloy: **6**, 59-68
Algebraic filtering operations: **12**, 1-10
Amorphous current transformer: **7**, 68-76
Amorphous silica: **10**, 66-73
Amorphous silicon: **11**, 68-77
Amplified spontaneous emission (ASE): **11**, 1-13
Analog image recording: **5**, 73-82
Anodic oxidation: **6**, 99-106
Antenna duplexer: **8**, 48-60
Asymmetric coplanar stripline (ACPS): **1**, 25-34
Asymmetry: **8**, 40-47
ATC: **8**, 40-47
Atomic force microscope (AFM): **12**, 99-110
Atomic-level epitaxy: **2**, 14-22
Attenuation characteristic: **5**, 27-34
Attenuation poles: **8**, 48-60
Autostereoscopic 3D display: **7**, 77-84
Autostereoscopic 3D television display: **8**, 89-98

Bandpass: **7**, 22-30
Barium ferrite: **2**, 108-113
Batch-process packaging: **1**, 93-106
$Ba_{1-x}K_xBiO_3$: **12**, 73-81
Beryllium doping: **6**, 34-41
Bi-CMOS: **3**, 105-113
BiPbSrCaCuO (BPSCCO) superconductor: **8**, 99-109
Biquad filter: **2**, 83-92
Body-effect compensation: **12**, 82-89
Boundary element method: **2**, 43-49
Breakdown voltage: **6**, 99-106
Buffer layer: **1**, 25-34

CAD: **7**, 1-11
Cadmium arachidate: **12**, 99-110
Calorimetry: **11**, 25-33
Capacitive pressure sensor: **1**, 93-106
Capacitive sensor: **4**, 73-83; **7**, 85-91
CCD: **3**, 43-51
Čerenkov instability: **1**, 42-50
Characteristic variation: **3**, 85-93
Chemical beam epitaxy: **6**, 34-41
Chemical oxidative polymerization: **6**, 88-99
Chiral nematic liquid crystal: **12**, 90-98
Cholesteric-nematic phase transition: **12**, 90-98
Circuit theory: **7**, 102-109
Co-Cr medium: **5**, 94-104
Coated magnetic film: **2**, 108-113
Collapse: **7**, 39-46
Colloid-SEM method: **10**, 58-65
Common memory: **2**, 1-13
Complex eigenstate: **3**, 28-35
Complex frequency variable: **7**, 102-109
Complex refractive index: **4**, 51-59
Complex-valued equivalent circuit: **7**, 102-109
Composite magnetic head: **3**, 94-104
Composite material device: **1**, 68-79
III-V Compound semiconductor: **2**, 14-22
Computer algebra: **1**, 1-12, 13-24
Computer simulation: **6**, 107-112
Conductor edges: **10**, 30-38
Conductor thickness: **9**, 1-10
Constant voltage step: **8**, 110-117
Contact material: **3**, 63-73
Cooling efficiency: **1**, 68-79
Coplanar stripline (CPS): **1**, 25-34
Coplanar waveguide (CPW): **1**, 25-34
Cost-performance analysis: **8**, 72-82
CO_2 laser corona preionization: **1**, 35-41
Crystal oscillator: **9**, 61-69
Crystal resonator: **9**, 61-69
Crystallinity: **7**, 95-101
Crystallization: **7**, 39-46
Crystallization phenomena: **10**, 108-116
Cu metallization technology: **2**, 93-100
Current conveyor: **2**, 83-92
Current density: **3**, 20-27
Current mirror: **3**, 105-113
Current sensor: **9**, 80-90
$CuTi_2$ intermetallic compound film: **2**, 93-100
CVD: **12**, 11-19

Damage: **6**, 69-77
Decision feedback: **4**, 84-95
Deep-level trap: **6**, 69-77
Demultiplexing: **7**, 22-30

Depth of focus: **11**, 106-114
Detuning characteristics: **4**, 22-31
Device simulation: **12**, 48-57
Dielectric coaxial resonator: **8**, 48-60
Dielectric disk resonator: **5**, 27-34
Dielectric grating: **3**, 10-19; **7**, 47-56
Dielectric material: **8**, 28-39
Dielectric multilayer bandpass filter: **2**, 57-68
Dielectric multilayer resonator: **2**, 57-68
Dielectric waveguide: **7**, 1-11
Dielectric-filled coaxial resonator: **2**, 31-42
Differential equation method: **3**, 10-19
Differential output: **8**, 83-88
Diffraction efficiency: **8**, 40-47
Diffused optical waveguide: **2**, 50-56
Diffusion barrier: **2**, 93-100
Digital magnetic recording: **3**, 52-62; **6**, 51-58
Digital recording characteristics: **5**, 73-82
Digital tape recorder: **5**, 83-93
Direct silicon nitrification: **3**, 74-84
Directional coupler: **7**, 22-30; **8**, 1-13
Disk array: **8**, 72-82
Display system: **11**, 43-58
Dissolution rate: **11**, 106-114
Distributed coupled line: **5**, 45-55
Double gate structure: **10**, 39-48
Downward diode decoder: **4**, 96-105
Drift current: **8**, 61-71
Driver LSI: **12**, 31-39
Dual-stage actuator: **3**, 94-104

Effective noise temperature: **6**, 78-87
Effective refractive index: **2**, 50-56
Eigenstate calculations: **2**, 101-107
Electrical contact resistance: **3**, 63-73
Electrical feedback: **3**, 1-9
Electrical perturbation: **2**, 69-82
Electrolytic polymerization: **6**, 88-99
Electromagnetic theory: **1**, 42-50
Electron beam-induced etching: **2**, 14-22
Electron wave: **5**, 56-62
Electron waveguide: **3**, 20-27
Electron waveguide discontinuity: **3**, 20-27
Electronic circuit: **2**, 83-92
Electronic shutter: **3**, 43-51
Elementary process and its chart: **8**, 14-27
Ellipsoidal mirror: **1**, 80-92
Elliptic function filter: **8**, 48-60
Erbium-doped fiber: **4**, 32-41
Erbium-doped fiber amplifier: **10**, 21-29
Erbium-doped optical fiber amplifier (EDFA): **11**, 1-13
Error rate: **3**, 94-104
Excimer laser: **12**, 40-47
Excimer laser annealing: **11**, 59-67
Excitation problem: **6**, 23-33
Extended ray theory: **8**, 14-27, 28-39
External electric field: **3**, 28-35
Extinction ratio: **4**, 51-59
Extrapolation: **7**, 57-67
Eye tracking: **11**, 43-58

Faraday effect: **5**, 1-10; **7**, 12-21
Feature extraction: **5**, 11-20
Feature-extracting optical neuron device: **5**, 11-20
Femtosecond pulse: **4**, 32-41
Fiber laser: **4**, 32-41
Filter: **5**, 45-55
Fine lithography technology: **6**, 42-50
Finite difference method: **5**, 35-44
Finite difference time-domain method: **9**, 1-10
Finite element method: **3**, 20-27, 36-42; **5**, 56-62; **6**, 23-33
Fishing effect: **8**, 99-109
Fixed pattern noise: **3**, 43-51
Fluoride glass: **7**, 39-46
FM recording characteristics: **5**, 73-82
Focus error detection: **1**, 80-92
Focus margin: **11**, 106-114
Fourier transform: **9**, 33-40
Frequency chirp: **10**, 21-29
Frequency control: **5**, 1-10
Frequency stabilization: **5**, 1-10; **7**, 12-21

GaAlAs laser diode: **4**, 13-21
GaAs integrated circuit: **9**, 100-111
GaInAsP/InP: **6**, 34-41
Gas evaporation method: **10**, 58-65
Gate insulator: **12**, 11-19
Gate insulators: **11**, 34-42
Gate oxide film: **9**, 91-99
Giant-scale microelectronics: **12**, 20-30
Grain boundary: **11**, 86-93
Grain boundary control: **10**, 99-107
Grain size distribution: **3**, 85-93
Green's function: **3**, 10-19

Head-to-medium magnetic interaction: **4**, 106-115
Heater bridge: **8**, 83-88
High-T_c superconducting oxide: **12**, 66-72
High-density recording: **5**, 73-82
High-efficiency power supply: **11**, 94-105
High-order modes: **7**, 57-67
High-resolution optical fiber length measurement: **11**, 25-33
High-sensitivity position detection: **3**, 94-104
High-speed movement: **8**, 61-71
High-speed SRAM: **4**, 96-105
Higher-mode cavity: **6**, 1-12
Histogram: **3**, 63-73

Humidity resistor: **7**, 85-91
Hybrid circuit: **8**, 1-13
Hybrid excitation: **3**, 74-84
Hybrid ring: **8**, 1-13
Hydrogen effusion rate: **7**, 92-94
Hydrogen radical excitation: **3**, 74-84
Hydrogenated amorphous silicon: **10**, 80-89

IBCO/PBCO/Au/Nb junction: **12**, 58-65

Image reconstruction: **9**, 33-40
Image sensor: **3**, 43-51; **11**, 68-77
In-situ lithography: **2**, 14-22
Induction susceptance: **6**, 69-77
Infrared absorption: **11**, 34-42
InGaAsP laser diode: **4**, 32-41
Injection excitation: **6**, 1-12
Injection locking: **4**, 22-31; **11**, 14-24
Injection seeding: **2**, 23-30
Inner structure: **4**, 13-21
Insertion loss: **4**, 51-59
Inside field: **6**, 107-112
Integral equation: **2**, 43-49; **3**, 10-19; **7**, 1-11
Integrated optical circuit: **4**, 42-50
Integrated optical filter: **7**, 22-30
Integrated sensor: **1**, 93-106
Intensity modulation: **11**, 1-13
Interface barrier: **7**, 92-94
Interface state: **6**, 99-106; **11**, 34-42
Interlevel dielectric: **6**, 59-68
Intermodal injection locking: **4**, 22-31
Interpolator: **4**, 84-95

Josephson current: **12**, 66-72
Josephson junction: **9**, 70-79; **11**, 86-93
Josephson mixer: **6**, 78-87

Kinetic inductance: **12**, 58-65
Kinoform: **9**, 41-49

Langmuir-Blodgett (LB) films: **12**, 99-110
Laser amorphization: **10**, 80-89
Laser annealing: **9**, 112-119; **10**, 90-98
Laser crystallization: **10**, 80-89
Laser diode: **4**, 1-12
Laser diode array: **10**, 10-20
Laser doping: **10**, 80-89
Lateral electric field: **8**, 40-47
Layered structure: **9**, 1-10
LC bandpass filter: **2**, 57-68
LC low-pass prototype: **2**, 57-68
LCD: **10**, 74-79; **12**, 40-47
LCD display: **7**, 77-84
LCD driver circuit: **12**, 31-39
Leaky wave: **6**, 13-22; **7**, 47-56

LED circuit: **7**, 68-76
Lenslet array: **10**, 1-9
Lenticular lens: **11**, 43-58
Lenticular system: **8**, 89-98
Lifetime of resonant state: **7**, 102-109
$LiNbO_3$: **2**, 50-56
Linear amplifying loop mirror: **4**, 32-41
Linear segment method (LSM): **2**, 50-56
Liquid crystal display: **11**, 59-67; **12**, 20-30, 40-47
Liquid SAW sensor: **2**, 69-82
Liquid-crystal video projector: **8**, 89-98
Liquid-phase deposition method: **11**, 34-42
Loaded Q: **2**, 57-68
Long term aging: **7**, 68-76
Long-range proximity effect: **12**, 58-65
Longitudinal magnetic recording: **3**, 94-104
Loss: **9**, 1-10
Low flow rate: **8**, 83-88
Low medium noise: **3**, 94-104
Low-energy ion beam etching: **8**, 110-117
LPCVD: **9**, 112-119
LSI contact structure: **2**, 93-100

Magnetic disk subsystem: **8**, 72-82
Magnetic domain measurement: **10**, 58-65
Magnetic field: **4**, 13-21
Magnetic flux: **8**, 99-109
Magnetic force microscope: **5**, 94-104
Magnetic material: **6**, 13-22
Magnetic recording: **6**, 107-112
Magnetic recording medium: **2**, 108-113; **10**, 58-65
Magnetization profile: **10**, 58-65
Magneto-optic waveguide: **7**, 31-38
Magnetooptic effect: **4**, 42-50
Magnetostatic surface wave: **4**, 42-50
Magnetostatic wave: **6**, 23-33
Manufacturing process line: **10**, 49-57
Mass loading effect: **2**, 69-82
Mass-flow sensor: **8**, 83-88
Massively parallel processing: **10**, 1-9
Mathematical programming: **8**, 72-82
MAX, MIN, and literal circuits: **3**, 105-113
Maximum entropy method: **9**, 33-40
MCVD method: **7**, 39-46
Memory: **4**, 60-72
Memory cell: **9**, 70-79
3D Memory LSI: **2**, 1-13
Mesoscopic quantum structures: **2**, 101-107
Metal film resistor: **5**, 105-114
Metallic contamination: **10**, 49-57
Metallic island films: **5**, 21-26
Metallization thickness: **10**, 30-38
Michelson interferometer: **11**, 25-33
Microchannel spatial light modulator (MSLM): **8**, 40-47

Microcrystallization time: **7**, 92-94
Micromachining: **4**, 73-83; **8**, 83-88
Micromechanics: **5**, 94-104
Microstrip line: **10**, 30-38
Microwave: **7**, 57-67; **9**, 11-20
Microwave circuit: **8**, 1-13
MIG-type ring head: **5**, 73-82
Miller compensation: **4**, 60-72
Millimeter wave: **7**, 57-67
Mobile communications: **6**, 42-50
Mobility: **10**, 66-73
Mobility model: **12**, 48-57
Mode-matching method: **10**, 30-38
Monolithic sensor: **7**, 85-91
Moving potential wall: **8**, 61-71
Multilayered diffraction grating: **9**, 21-32
Multilayered waveguide: **4**, 42-50
Multilevel interconnection: **6**, 59-68
Multimode laser diode: **11**, 25-33
Multiple-device oscillator: **6**, 1-12
Multipole expansion: **3**, 36-42
Multivalued logic circuit: **3**, 105-113

Nanobridge: **6**, 78-87
Nb-doped $SrTiO_3$: **12**, 73-81
Nd:YAG laser: **2**, 23-30
Nd:YVO_4 laser: **2**, 23-30
Network theory: **1**, 107-113
Noncontact sensor: **9**, 80-90
Nonelectrolytic plating: **5**, 105-114
Nonlinear amplifying optical loop mirror: **10**, 21-29
Nonreciprocal phase shift: **7**, 31-38
Nontracking method: **5**, 83-93
Numerical analysis: **7**, 1-11, 31-38; **8**, 61-71

Oblique incident evaporation: **8**, 110-117
Oblique propagation: **7**, 47-56
Odor-pattern recognition: **12**, 110-115
Off current: **10**, 74-79
Off-axis sputtering: **11**, 78-85
Open-type waveguide: **3**, 36-42
Optical anisotropy: **5**, 21-26
Optical coupling characteristics: **10**, 10-20
Optical directional coupler: **2**, 50-56
Optical disk: **1**, 80-92
Optical feedback: **11**, 14-24
Optical fiber: **1**, 1-12, 13-24; **7**, 39-46; **10**, 10-20
Optical fiber bundle: **1**, 80-92
Optical fiber communications: **10**, 10-20
Optical fiber sensor: **11**, 25-33; **12**, 110-115
Optical filter: **11**, 1-13
Optical frequency domain reflectometry (OFDR): **9**, 33-40
Optical integrated circuit: **5**, 35-44; **7**, 31-38
Optical interconnection: **2**, 1-13
Optical memory: **1**, 51-59, 60-67
Optical mode conversion: **4**, 42-50
Optical modulator: **4**, 1-12
Optical neural network: **5**, 11-20; **10**, 1-9
Optical neuron device: **10**, 1-9
Optical pickup: **1**, 80-92
Optical propagation characteristic: **7**, 95-101
Optical soliton: **10**, 21-29
Optimal configuration: **8**, 72-82
Optimum structure design: **2**, 31-42
Optoelectric integrated circuit: **2**, 14-22
Organic insulator: **12**, 66-72
Organic vapor recognition: **12**, 110-115
Oscillator: **5**, 45-55
Overturning: **12**, 99-110
Overwrite: **6**, 107-112
Oxygen reduction: **5**, 105-114

Package resin: **6**, 59-68
Parallax barrier method: **7**, 77-84
Parallel processing: **2**, 1-13
Parametric oscillation: **9**, 80-90
Partial response: **4**, 84-95
Partial response system: **6**, 51-58
Particle analysis: **10**, 49-57
Pattern recognition: **5**, 11-20
Peltier effect: **1**, 68-79
Periodic condition: **3**, 10-19
Periodic structure: **6**, 13-22
Perpendicular magnetic recording: **2**, 108-113; **4**, 106-115; **5**, 94-104
Perturbation method: **1**, 13-24
Phase change: **1**, 51-59, 60-67
Phase compensation: **4**, 60-72
Phase control: **11**, 94-105
Phase matching: **9**, 41-49
Phase retrieval problem: **9**, 41-49
Phase shift: **9**, 11-20
Phase shifter: **9**, 11-20
Phase-recording characteristics: **9**, 41-49
Photo-CVD SiO_2: **9**, 100-111
Photodetector array: **10**, 10-20
Photoelectric device: **11**, 68-77
Photoexcitation: **3**, 74-84
Photonic integrated circuit: **4**, 1-12
Photoresist: **11**, 106-114
PIN diode: **9**, 11-20
Pinning center: **8**, 99-109
Planar electron waveguide: **5**, 56-62
Planar grating: **6**, 13-22
Planar microlens (PML): **10**, 10-20
Plane wave diffraction: **9**, 21-32
Plasma doping: **11**, 59-67
Plating bath treatment: **5**, 105-114
Polarizer: **5**, 21-26

Poly-Si TFT: **9**, 91-99, 112-119; **11**, 59-67
Polycrystalline silicon: **10**, 80-89, 99-107; **12**, 40-47, 48-57
Polycrystalline silicon thin film transistor: **10**, 108-116
Polyimide: **6**, 59-68
Polymer network: **12**, 90-98
Polymer-dispersed liquid crystal: **12**, 90-98
Polynomial refractive index profile: **1**, 1-12, 13-24
Polypyrrole solid electrolyte: **6**, 88-99
Polysilicon: **3**, 85-93
Post-hydrogenation: **10**, 66-73
Potential-sensitive dye coating: **12**, 110-115
Power combining: **6**, 1-12
Power divider: **5**, 35-44
Preparation of Poly-Si: **10**, 90-98
Profile simulation: **11**, 106-114
Proton beam: **10**, 108-116
Pulsed laser: **1**, 35-41
Pushed-against junction: **11**, 78-85

Quantum box structure: **3**, 28-35
Quantum effect: **11**, 86-93
Quantum well: **5**, 56-62
Quantum wire: **3**, 20-27
Quantum wire structure: **2**, 101-107
Quaternary logic gate: **12**, 82-89

RAM: **4**, 60-72
Rat-race circuit: **8**, 1-13
Ray tracing: **8**, 14-27; **11**, 43-58
Ray tube: **8**, 28-39
Rb absorption line: **5**, 1-10; **7**, 12-21
Reactive ion etching (RIE): **6**, 69-77
Read equalization: **3**, 52-62
Recording: **6**, 107-112
Reflection coefficient: **5**, 63-72
Relative pressure sensor: **7**, 85-91
Remote plasma CVD: **10**, 80-89
Residual stress: **4**, 73-83
Resin stress: **6**, 59-68
Resonance level: **5**, 63-72
Resonant absorption: **5**, 21-26; **9**, 21-32
Resonant electrical length: **2**, 31-42
Resonant order: **5**, 27-34
Resonant tunneling: **5**, 63-72
Resonant tunneling effect: **1**, 107-113
Resonant wavelength: **5**, 27-34
Resonator: **5**, 45-55
Response: **10**, 74-79
Returning light: **11**, 14-24
RF plasma source: **10**, 108-116
Rotational head: **5**, 83-93

Sample format: **1**, 51-59, 60-67
Saturated absorption spectroscopy: **7**, 12-21
Scalar finite-element method: **7**, 31-38
Scalar wave equation: **1**, 1-12
Scanning probe microscope: **5**, 94-104
Scattering: **7**, 1-11
Scattering problem: **2**, 43-49
Schottky barrier: **12**, 73-81
Schottky barrier CCD: **8**, 61-71
Schottky barrier diode (SBD) decoder: **4**, 96-105
Selective growth: **4**, 1-12
Self-activation: **10**, 108-116
Self-alignment: **10**, 99-107
Self-heating effect: **6**, 78-87
Self-injection: **11**, 14-24
Semiconductor laser: **3**, 1-9; **4**, 13-21, 22-31; **5**, 1-10; **7**, 12-21; **11**, 14-24
Semiconductor superlattice: **1**, 107-113
Separated configuration of read/write head: **4**, 106-115
Shear-horizontal SAW device: **2**, 69-82
Shift register: **11**, 68-77
Short-channel effect: **12**, 48-57
Signal processing: **3**, 94-104; **6**, 51-58
Silicon nitride film: **4**, 51-59
Silver oxide: **8**, 99-109
Simulation: **3**, 85-93
Single-mode oscillation: **2**, 23-30
Single-pole head: **4**, 106-115
Sintering method: **2**, 108-113
SiO_2: **9**, 91-99
SIO_2: **12**, 11-19
Sliding contact: **4**, 106-115
Small disk: **8**, 72-82
Small-size, lightweight power supply: **11**, 94-105
Smith chart: **1**, 107-113
Smith-Purcell free electron laser instability: **1**, 42-50
Smith-Purcell radiation: **1**, 42-50
Smooth film: **9**, 50-60
Sol-gel method: **9**, 50-60
Solidification rate: **10**, 90-98
Soliton: **11**, 1-13
Spectral-domain filtering: **12**, 1-10
Spectroscopic ellipsometry: **9**, 100-111
Spin density: **9**, 112-119
Spontaneous emission: **10**, 21-29
Sputtering: **7**, 95-101; **9**, 91-99
Step edge: **11**, 86-93
Stepwise frequency sweeping: **3**, 1-9
Stereoscopic image: **11**, 43-58
Stopband: **7**, 47-56
Stretching method: **5**, 21-26
Stripline: **5**, 45-55
Suboxide: **6**, 99-106
Superconducting device: **11**, 86-93
Superconducting-base transistor: **12**, 73-81

Superconductivity: **9**, 70-79
Surface acoustic wave: **6**, 42-50
Surface resistance: **6**, 13-22
Surface-emitting layer: **6**, 34-41
Surface-protective layer of SiO_2: **9**, 100-111
Switched-capacitor power supply: **11**, 94-105
Switching cutoff frequency: **9**, 11-20
Switching regulator: **11**, 94-105
Symmetric double-barrier structure: **5**, 63-72
Synchronous digital circuit: **4**, 84-95
Synthesis: **5**, 63-72
Synthesis of resonant levels: **1**, 107-113

Tantalum electrolytic capacitor: **6**, 88-99
Tantalum oxide: **9**, 50-60
Taper: **7**, 57-67
3D Television: **7**, 77-84
3D Television not requiring special glasses: **8**, 89-98
Temperature change: **3**, 1-9
Temperature-compensated crystal oscillator: **9**, 61-69
TFD: **10**, 74-79
TFT: **12**, 11-19, 40-47
Thermal analysis: **1**, 51-59, 60-67
Thermal conduction: **7**, 39-46
Thermal expansion coefficient: **6**, 59-68
Thermal recording: **1**, 51-59, 60-67
Thick-film structure: **1**, 68-79
Thin film diode: **12**, 20-30
Thin film microstrip line: **9**, 1-10
Thin film transistor: **3**, 74-84, 85-93; **10**, 66-73, 90-98, 99-107; **11**, 68-77; **12**, 20-30, 40-47, 48-57
Thin film transistor (TFT) LCD: **12**, 31-39
Thin-film waveguide polarizer: **4**, 51-59
Threshold detector: **3**, 105-113
Threshold voltage: **10**, 66-73
Ti:$LiNbO_3$ optical modulator: **1**, 25-34
TM mode analysis: **2**, 31-42
Tracking: **5**, 83-93
Transfer loss: **3**, 43-51
Transient phenomena: **7**, 102-109
Transient scattering: **8**, 14-27, 28-39
Transistor analysis: **10**, 39-48
Transistor fabrication: **10**, 39-48
Transmission problem: **6**, 23-33
Trap level: **10**, 74-79
Tunnel junction: **12**, 66-72, 73-81
Tunneling Josephson device: **11**, 78-85
Two-dimensional optical phase modulation: **8**, 40-47
Two-port crystal resonator: **9**, 61-69
Two-wire detection method: **1**, 93-106
Two-wire direction: **4**, 73-83

ULSI: **10**, 49-57
Ultrahigh-density recording technology: **3**, 94-104
Undesired mode suppression: **6**, 1-12
Unidirectional surface acoustic wave device: **6**, 42-50
Uniform asymptotic solution: **1**, 1-12
Universal literal: **12**, 82-89
Unloaded Q: **2**, 31-42
Upward diode decoder: **4**, 96-105

Variable threshold: **12**, 82-89
Variable-thickness bridge (VTB) device: **8**, 110-117
Vector wave equation: **1**, 13-24
Very-short-channel MOS transistor: **10**, 39-48
Viscosity effect: **2**, 69-82
Viscous flow: **7**, 39-46
Viterbi decoding: **4**, 84-95
Voltage limiter: **4**, 60-72
Voltage-controlled crystal oscillator: **9**, 61-69
V_t shift: **11**, 68-77

Wafer bonding: **2**, 1-13
Waveguide: **7**, 57-67
Waveguide problem: **2**, 43-49
Wavelength division multiplexing (WDM): **4**, 1-12
Wavelength shift: **4**, 13-21
Weighted potential method: **3**, 28-35
Whispering gallery mode: **5**, 27-34
Wiener-Hopf technique: **12**, 1-10
Write equalization: **3**, 52-62

X-ray photoelectron spectrum: **6**, 99-106

Yasuura method: **9**, 21-32
YBaCuO thin film: **8**, 110-117
$YBa_2Cu_3O_x$ thin film: **11**, 78-85
YBCO/Au/Nb junction: **12**, 58-65

ZnO thin film: **7**, 95-101